

SUBMITTAL DATA SHEET



<b>Multi Zone Heat Pump</b>	
Location: _____ Engineer: _____ Submitted to: _____ Submitted by: _____ Reference: _____	Approval: _____ Date: _____ Construction: _____ Unit #: _____ Drawing #: _____

<b>Set Code</b>	22022310003204
Indoor unit code	22022011016623
Outdoor unit code	22022316001305
<b>Set Model</b>	
Indoor unit model	MIU-A09W-2
Outdoor unit model	MOU-4A36G-2
<b>Certified</b>	
AHRI	
UL	



SYSTEM PERFORMANCE DATA			
<b>Power supply</b>			
Normal Operational Voltage	(V, Ph, Hz)	208/230V, 1Ph, 60Hz	
Voltage Range	(V)	187-253	
<b>Electrical</b>			
Minimum circuit ampacity	(A)	25.0	
Max.fuse	(A)	40.0	
Connection wiring		14AWG*4 Stranded, unshielded	
<b>Cooling</b>			
Capacity	(Btu/h)	36000(9200-40160)	
Power Input	(W)	3396(340-4180)	
Current	(A)	15.4(2.9-18.3)	
SEER2	(Btu/W)	23.1	
EER2	(Btu/W)	10.6	
<b>Heating</b>			
Capacity	(Btu/h)	37000(8500-46600)	
Power Input	(W)	3098(480-4460)	
Current	(A)	15.4(3.4-19.5)	
HSPF2-4	(Btu/W)	9.6	
HSPF2-5	(Btu/W)	7.2	
COP	W/W	3.50	
Heat at 17F(H32)	(Btu/h)	26400	
Heat at 5F(H42)	(Btu/h)	24000	
COP at 5F(H42)	W/W	1.80	

Outdoor(cooling)	(Deg. °F )	5~122
	(Deg. °C)	-15~-50
Outdoor(heating)	(Deg. °F )	-13~-75
	(Deg. °C)	-25~-24

REFRIGERANT PIPE DATA		
Design pressure	(PSIG)	550/340
Refrigerant Type		R410A
Refrigerant charge	oz	134.0
Refrigerant precharge	(ft)	25x4
Additional charge for each ft (Φ 6.35 (1/4") liquid pipe)	(oz/ft)	0.16
Additional charge for each ft (Φ 9.52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	4x1/4"
	(mm)	4x6.35
Gas side	(inch)	3x3/8"+1x1/2"
	(mm)	3x9.52+1x12.7
Max. length for all rooms	(ft)	262.5
	(m)	80.0
Max. length for one indoor unit	(ft)	114.8
	(m)	35.0
Max. height difference between indoor and outdoor unit	(ft)	49.2
	(m)	15.0
Max. height difference between indoor units	(ft)	33.0
	(m)	10.0

OUTDOOR UNIT DATA		
<b>Compressor</b>		
Type		ROTARY
Model		KTF310D43UMT
Brand		GMCC
Capacity	(Btu/h)	34154
Input	(W)	2765
Rated current (RLA)	(A)	18
Refrigerant oil/oil charge	(ml)	VG74/1000
<b>Outdoor fan motor</b>		
Model		ZKFN-120-8-2
Qty		1
Input	(W)	150.00
Output	(W)	120.00
RLA	(A)	1.00
Speed	(r/min)	1000/900/750
<b>Air flow &amp; Noise level</b>		
Outdoor air flow (Max.)	(CFM)	2147.06
Outdoor noise level	[dB(A)]	63.50
<b>Outdoor unit</b>		
Dimension (W×D×H)	(inch)	37.24x16.14x31.89
	(mm)	946x410x810
Packing (W×D×H)	(inch)	42.91x19.69x34.84
	(mm)	1090x500x885
Net/ Gross weight	(lbs.)	169.09/181.44
	(kg)	76.7/82.3

Outdoor unit dimension

